

## Power Turtle X CPTSX-T1-T7 (U.S.)

1x powerCON TRUE1 IN – 7x powerCON® TRUE1® TOP OUT - Indoor (NEMA1)



EU version: Power Turtle X CPTX-T1-T7

Power Turtle Xtreme Outdoor (XO) is a compact distribution solution for mobile applications. Rugged EASYLEN® housing is ideally suited for demanding applications and harsh conditions. 1x powerCON® TRUE1® TOP In and 7x powerCON® TRUE1® TOP Out.



COMING SOON!



**Intertek**

## Features & Benefits

- Extreme robust and safe EASYLEN® housing with leather grain texture
- Highly reliable NEUTRIK® powerCON® TRUE1® TOP recepticals for In, Out and Daisy chaining
- Flame retardant (UL94-V0) and non-conductive housing material
- High mechanical protection (high IK)
- Light weight, compact, lower height (Power Turtle) and stackable housing design
- Versatile mounting options

## Market & Application

- Markets. Professional video wall / lighting / audio
- Mobile application. Festivals, live events
- Semi-permanent applications. Theaters, studios

## Article order data

Article name	Details	Order code
CPTSX-T1-T7	IN: powerCON® TRUE1® TOP OUT: 7x powerCON® TRUE1® TOP Indoor (NEMA1)	1035610

## Technical Information

Product	
<b>Input device</b>	1x powerCON® TRUE1® TOP
<b>Output device</b>	7x powerCON® TRUE1® TOP
<b>Daisy chaining</b>	1x powerCON® TRUE1® TOP

Electrical	
<b>Contact resistance / protection class</b>	Protection class II
<b>Dielectric strength</b>	0.5 kV / mm
<b>Rated voltage</b>	120V AC
<b>Rated Current</b>	20A
<b>Number of electrical contacts</b>	2 + PE
<b>Phases</b>	single-phase

Mechanical	
<b>Lifetime</b>	> 5000 Mating cycles
<b>Dimensions</b>	220 x 150 x 65 mm
<b>Conductor cross section</b>	AWG12
<b>Weight</b>	1.0 kg
<b>Mounting options</b>	Truss clamp, mounting wholes for pegging or suspension
<b>Type of construction</b>	Stackable

## Material

<b>Housing</b>	Easylen
<b>Color</b>	black

## Environmental

<b>Standards compatibility</b>	UL94-V0
<b>Protection class</b>	NEMA1 listed. IP20.
<b>Temperature range</b>	-25 °C to +70 °C

## Compliance

<b>Standard Compliance</b>	ETL Listed. Compliant to UL STD 1640
----------------------------	--------------------------------------