


Power Container Xtreme Outdoor CPC32-C1C2T3F3-RB

On request modification.

Power Container is a highly reliable, rugged and first level powerful distribution solution.





Features and Benefits

- High durability & protection: rugged
 Easylen® housing with high IK, IP44 with
 all connectors in mated condition, self closing caps, connector protection, flame
 retardant & non-conductive housing
 material
- High quality of component and assembly add to high reliability and safety of the power distribution and the event

Easy transport & handling: compact, stackable, fully lockable, integrated handles

Markets & Applications

- Markets: LED walls, Lighting, Other
- Mobile applications: Festivals, live events
- Semi-permanent applications: Theaters, studios, fairs

Order information

Product title	Details	Order code
CPC32-C1-C2T3F3-RB	Please see the drawing and technical information below.	1038191



Technical Information

Product	
Input device	1x CEE32A 5P red (1x RCD40A C 4P)
Output device	2x CEE 16A 5P (1x MCB16A C 3P) 3x PowerCON TRUE1 TOP & 3x Schuko F Type (6x MCB16A C 1P) 1x RCCB 40A 30mA 4P 1x cPot
Main switch	-
Power meter	-

Electrical		
Phase control indicator	L1, L2, L3, green	
Rated voltage	415V/AC, 50Hz	
Rated Current	In: 32A	

Mechanical	
Type of construction	Stackable
Dimensions	ca. 395 x 295 x 270 mm

Material	
Housing	Easylen®
Color	black



Environmental	
Protection class	IP44 with CEE and cPot in mated condition
Temperature range	-5 °C to +40 °C