



Power Container Xtreme Outdoor CPC63-C1- C4T3F3-RB

On request modification.

Power Container is a highly reliable, rugged and first level powerful distribution solution.



Features & Benefits

- **High durability & protection:** rugged Easylen® housing with high IK, IP44 with all connectors in mated condition, self-closing caps, connector protection, flame retardant & non-conductive housing material
- **Easy transport & handling:** compact, stackable, fully lockable, integrated handles
- **High quality of component and assembly** add to high reliability and safety of the power distribution and the event

Markets & Applications

- Markets: LED walls, Lighting, Other
- Mobile applications: Festivals, live events
- Semi-permanent applications: Theaters, studios, fairs

Order information

Product title	Details	Order code
CPC63-C1-C4T3F3-RB	Please see the drawing and technical information below.	1038196

Technical Information

Product	
Input device	1x CEE63A 5P red
Output device	2x CEE 32A 5P (2x MCB32A C 3P, 1x RCD63A 30mA 4P) 2x CEE 16A 5P (2x MCB32A C 3P) 3x PowerCON TRUE1 TOP & 3x Schuko F Type (6x MCB16A C 1P) 1x RCD 63A 30mA 4P 1x cPot
Main switch	-
Power meter	-

Electrical	
Phase control indicator	L1, L2, L3, green
Rated voltage	415V/AC, 50Hz
Rated Current	In: 63A

Mechanical	
Type of construction	Stackable
Dimensions	ca. 395 x 295 x 405 mm

Material	
Housing	Easylen®
Color	black

Environmental

Protection class	IP44 with CEE and cPot in mated condition
Temperature range	-5 °C to +40 °C