



# Power Container Xtreme Outdoor CPC63-C2- C2T3F3-RB

On request modification.

Power Container is a highly reliable, rugged and first level powerful distribution solution.

## Features and Benefits

- **High durability & protection:** rugged Easylen® housing with high IK, IP44 with all connectors in mated condition, self-closing caps, connector protection, flame retardant & non-conductive housing material
- **Easy transport & handling:** compact, stackable, fully lockable, integrated handles
- **High quality of component and assembly** add to high reliability and safety of the power distribution and the event

## Markets & Applications

- Markets: LED walls, Lighting, Other
- Mobile applications: Festivals, live events
- Semi-permanent applications: Theaters, studios, fairs

## Order information

Product title	Details	Order code
CPC63-C2-C2T3F3-RB	Please see the drawing and technical information below.	1038189

## Technical Information

Product	
Input device	1x CEE63A 5P red
Output device	1x CEE63A 5P red (-)  1x CEE 32A 5P (1x MCB32A C 3P, 1x RCCB 40A 30mA 4P) 1x CEE 16A 5P (1x MCB16A C 3P, 1x RCCB 40A 30mA 4P) 3x PowerCON TRUE1 TOP & 3x Schuko F Type (6x MCB16A C 1P, 1x RCCB 40A 30mA 4P)  1x cPot
Main switch	-
Power meter	-

Electrical	
Phase control indicator	L1, L2, L3, green
Rated voltage	415V/AC, 50Hz
Rated Current	In: 63A

Mechanical	
Type of construction	Stackable
Dimensions	ca. 395 x 295 x 405 mm

Material	
Housing	Easylen®
Color	black

## Environmental

<b>Protection class</b>	IP44 with CEE and cPot in mated condition
<b>Temperature range</b>	-5 °C to +40 °C