



# Multipin 1 Multipin 2 1 2 3 4 5 6 1 2 3 4 5 6 1 2 3 4 5 6 1 2 3 4 5 6 1 2 3 4 5 6 1 2 3 4 5 6 1 2 3 4 5 6 1 2 3 4 5 6 1 2 3 4 5 6 1 2 3 4 5 6 1 2 3 4 5 6 1 2 3 4 5 6 1 2 3 4 5 1 1 2 3 4 5 6 1 2 3 4 5 1 1 1 1 1 1 1 1 1 1 1 1

# POWER RACK XTREME CPRX63-C1-H4T6-ROM

On request modification.

IN: Input cable 2m 1x CEE63A, OUT: 4x Harting E16, 6x powerCON TRUE1 TOP.

Power Rack Xtreme is a powerful and highly reliable distribution solution for installation in the 19" Rack. It is ideally suited for amplifier rack wiring application.

#### **Features & Benefits**

- High quality electrical and electronical component from the renowned brands
- High quality assembly in EU

- Circuit protection with residual current device (RCCB) and miniature circuit breakers (MCB)
- Attractive price / value ratio



### **Markets & Applications**

- Markets: Professional audio esp. amp rack wiring / lighting / video wall
- Mobile applications: Festivals, live events. Control panels / rooms.
- Semi-permanent applications: Theaters, studios, fairs. Control panels /rooms.

#### **Ordering information**

Article name	Details	Order code
CPRX63-C1-H4T6- ROM	Front: 24x RCBO (1-pole+N), 1x measuring device Selec MFM 384, 1x main switch 4-pin, Back: IN: 1x Input cable 2m with CEE63A, OUT: 4x Harting E16, 6x powerCON TRUE1 TOP	1038252



## **Technical Information**

Product	
Input device	IN: 1x Input cable 2m with CEE63A
Daisy chain	
Output device	4x Harting E16 6ch [1-9] 24x RCBO (1-pole+N) 6x powerCON TRUE1 TOP (parallel to Harting 1) 1x cPot
Main switch	1x main switch 4-pin
Power meter	1x Selec MFM 384

Electrical	
Phase control indicator	
Rated voltage	400V
Rated Current	63A

Mechanical	
Weight	
Type of construction	19" Housing 6 HE

Material	
Housing	Metal
Color	Black



Environmental		
Protection class	IP20	
Temperature range	-5 to +40°C	